

**EXCLUSIVE** 

# SPIDER LIFTS AT A HIGHER LEVEL FOR 40 YEARS

FS 370 / FS 420





# The ultimate compact platform.

The Falcon Spider Atrium Lift FS 370/420 is an original Falcon Spider Lift with market leading features. These Falcon Spider Atrium Lifts have a 37-42 m working height, and is designed with wheels for smooth propelling and reduced ground pressure. The Falcon Spider Atrium Lift was originally invented at first in the 1970's, and developed ever since. The Falcon Spider Atrium Lift FS 370/420 is very applicable in matters of:


- Facility management
- Atrium access
- Narrow access
- Best quality & safety
- Double jib system
- Easy transport & propelling
- Low weight & ground pressure
- Flexible outrigger setting
- Limited setup space
- Power Bi-energy Hybrid

The Falcon Spider Atrium Lift is capable of passing through a door opening a mere 0,9 m wide and 1,98 m high.



The special designed boogie axle with twin wheels reduces ground pressure and allows driving on sensitive floorings.


## **FS 370**





Working height and reach To the outermost points.

## FS 420





Working height and reach To the outermost points



Model: FS 370 FS 420

Working height: 37 m 42 m Maximum reach: 16-17 m 16-17 m

Double jib (2 x 3 m): 6 m 6 m Double jib rotation: 200° 200° Basket load: 200 kg 200 kg Aluminium basket:  $(0.8 \times 1.4 \text{ m})$  $(0.8 \times 1.4 \text{ m})$ Basket rotation (option): +/- 90° +/- 90° 375° Turret rotation: 375°

Dimensions (transport position)

 Total height:
 1,98 m
 1,98 m

 Total length:
 8,10 m
 8,25 m

Total width: 0,90 m\* - 1,80 m\* 0,90 m\* - 1,80 m\*

Gradability (standard): 10° / 20% 10° / 20% Weight approx.: 6.900 kg\* 7.500 kg\*

\*Depending on optional equipment





#### FALCON LIFTS A/S

Tolderlundsvej 106 DK-5000 Odense C Tel: +45 66 13 11 00

falcon@falconlifts.com falconlifts.com

#### STANDARD EQUIPMENT:

- Automatic stability & outreach control
- Computer controlled (can-bus)
- Proportional control of all functions
- Self-propelled
- Battery powered with charger (360 Ah)
- Double jib
- 375° turret rotation, with integrated stop
- Individual setting of each outrigger
- Electronic checking of the power system (PLC)
- Manual pump system for emergency lowering
- Ability to self-load onto trucks or trailers
- Non marking solid tyres
- Adjustable wheel-axle
- Minimum width only 0.9 m
- Space for tools etc. in basket
- Storage room with lock in chassis
- Boogie axle (reduces ground pressure)
- 4-wheel drive (2 axles)
- Wireless remote control of all functions
- Gradability (10° / 20%)
- Falcon Service Tool (remote access via laptop)

#### **OPTIONS:**

- +/- 90° basket rotation
- 220V AC power supply in the basket
- Air / water supply in the basket
- Sensor system on basket
- Diesel engine
- Anemometer wind warning system
- 400V AC direct powered electro motor
- 4-8 pcs extra batteries
- Autosetting/levelling
- Chassis control from basket
- Special outrigger footplates
- Basket in various sizes
- Slope alarm
- Twin wheels on rear axle
- Special colour
- Height control switch
- Cover
- GSM module for remote access and monitoring
- Anti entrapment device